


Videoscopes P1 & Rugged | compatible **video** probes...

Video Probe type	Part No	Ø mm	Working length (m)	Field of view	Direction of vision	Focussing range mm	Articulation	Resolution pixels
ARTICULATING VIDEO PROBES								
2-way articulating probe <i>metal braided</i>	P1-2XF28	2,8	1 & 1.5	80°	0°	10-50	2x180°	160.000
2-way articulating probe <i>metal braided</i>	P1-2XF3	3,0	1 & 2	80°	0°	10-50	2x180°	160.000
2-way articulating probe <i>PVC covering</i>	P1-2XF4	4,0	1 & 2	67°	0°	20-70	2x150°	300.000
	P1-2XF6	6,0	1,2 & 3	67°	0°	20-70 / 70-∞	2x150°	380.000
4-way articulating probe <i>PVC covering</i>	P1-4XF6	6,0	1,2 & 3	67°	0°	20-70	4x150°	380.000
	P1-4XF8	8,0	1,2 & 3	67°	0°	20-70 / 70-∞	4x150°	380.000
2-way articulating probe - Short tip - <i>PVC covering</i>	P1-2XF4-ES	4,0	1 & 2	90°	0°	20-70	2x160°	300.000
	P1-2XF6-ES	6,0	1 & 2	67°	0°	20-70	2x160°	380.000
2-way articulating probe high sensitivity - <i>metal braided</i>	P1-2XF4-HR	4,0	1 & 2	67°	0°	20-70	2x180°	400.000
	P1-2XF6-HR	6,0	1,2 & 3	67°	0°	20-70	2x180°	450.000
4-way articulating probe high sensitivity - <i>metal braided</i>	P1-4XF6-HR	6,0	1, 2	90°	0°	10-50	4x180°	450.000
2-way articulating probe infrared <i>metal braided</i>	P1-2XF9-IR	9,0	1,2 & 3	67°	0°	60-∞	2x180°	420.000
2 WAY rigid articulating probes	P1-2XR6	6,0	300,450 & 700 mm	67°	0°	20-70	2x180°	400.000
	P1-2XR8	8,0	450 & 700 mm	67°	0°	20-70 / 60-∞	2x180°	400.000
NON ARTICULATING VIDEO PROBES								
High sensitivity Probe <i>PVC covering</i>	P1-F39-HR	3,9	1,2,3 & 5	110°	0°	10-50	-	400.000
Flexible probe <i>PVC covering</i>	P1-F4	4,0	1,2,3,5 & 10	67°	0°	20-70	-	300.000
	P1-F55	5,5	1,2,3,5 & 10	67°	0°	20-70	-	400.000
Semi rigid probe <i>PVC covering</i>	P1-SR55	5,5	1,2 & 3	67°	0°	20-70	-	400.000
	P1-SR8	8,0	1,2 & 3	67°	0°	20-70	-	400.000
	P1-SR12	12,0	1 & 2	67°	0°	80-∞	-	400.000
	P1-SR16	16,0	1 & 2	67°	0°	80-∞	-	400.000
Dual Vision 0° & 90° <i>PVC covering probe</i>	P1-FDUAL	5,8	1,2,3,5,10, 20 & 30	67°	0°&90°	20-70	-	400.000
High sensitivity Probe stainless steel braided	P1-FGM55	5,5	1,2,3,5,10, 20 & 30	67°	0°	20-70	-	450.000
Rigid videoscope probe	P1-R39	3,9	302, 430 & 550 mm	67°	0°	20-70	-	300.000
	P1-R6	6,0	302, 430 & 550 mm	67°	0°	20-70	-	400.000
SPECIALTY VIDEO PROBES								
3 bars waterproof probe	P1-CW6	5,5	30	67	0°	20-70	-	400.000
	P1-CW14	14	30	67	0°	70-∞	-	400.000
Pipe inspection probe	P1-C28	28	30	67	0°	70-∞	-	400.000
Extension video Pole	P1-EXT-P	28	1.2 - 4m	70	0°	80-∞	-	400.000



- **Short focussing CF (10-50mm or 20-70mm)**
For close range inspection of details and narrow spaces

Our video probes are available in 2 focussing ranges



- **Long focussing LF (60/70mm to infinity)**
For panoramic inspection of larger areas and larger volumes.